

966-01 / 966-10A

Turbidi Meter (탁도계)



966-01



966-10A

966-01 특징

- 직접 판독 기능, 디지털 화면
- 범위 0~20, 0~200, 0~1,000 NTU 에서 0.01 NTU까지 분석가능
- 혼합, 희석 불필요
- 모든 형태의 액체의 투명도와 탁도 측정
- 신뢰성 있는 측정값

966-01 용도

- 정수장, 산업폐수, 방류수
- 음식과 음료, 화장품, 약품, 제지업
- 먹눈물, 음용수
- 호수, 강, 하천 등의 유출수

966-10A 특징

- 직접 판독 기능, 디지털 화면
- 범위 0~20, 0~200, 0~1,000 NTU 에서 0.01 NTU 까지 분석가능
- 혼합, 희석 불필요
- 모든 형태의 액체의 투명도와 탁도 측정
- 신뢰성 있는 측정값

966-10A 용도

- 정수장, 산업폐수, 방류수
- 음식과 음료, 화장품, 약품, 제지업
- 먹눈물, 음용수
- 호수, 강, 하천 등의 유출수

SPECIFICATIONS

사양 / 제품번호	966-01
Ranges & Sensitivity	Low : 0.00 to 19.99 NTU, resolution 0.01 NTU Medium : 0.00 to 199.9 NTU, resolution 0.1 NTU High : 000 to 999 NTU, resolution 1 NTU
Readout	LCD with automatic decimal point shift
Accuracy	± 2% of reading for low and medium ranges
Repeatability	± 1%
Power	4 inexpensive AA alkaline batteries (over 700 tests) Optional 110 / 220 volt AC adapters
Sample Volume	15 mL
Sample	Optically reproducible 28mm OD × 61mm glass vial with screw cap.
Permanent	USEPA approved primary, non-hazardous, 40 NTU

SPECIFICATIONS

사양 / 제품번호	966-10A
Ranges & Sensitivity	Low : 0.00 to 19.99 NTU, resolution 0.01 NTU Medium : 0.00 to 199.9 NTU, resolution 0.1 NTU High : 000 to 999 NTU, resolution 1 NTU
Readout	LCD with automatic decimal point shift
Accuracy	± 2% of reading for low and medium ranges
Repeatability	± 1%
Power	4 AA alkaline batteries (over 700 tests) Optional 110 / 220 volt AC adapters Switch - adjustable for 100/220v, 50/60Hz
Sample Volume	15 mL
Sample	Optically reproducible 28mm OD × 61mm glass vial with screw cap.
Permanent	USEPA approved primary, non-hazardous, 40 NTU

CONFIGURATIONS

966-51 Package of zero and 40 NTU Standards
966-50 Package
- 6 Sample Tubes
- 4 AA Batteries
- Instruction manual
- 966-CC Rugged Foam-lined Carrying Case.

CONFIGURATIONS

965-10A Direct-reading Turbidimeter
Complete with Package of zero and 40 NTU Standards
965-50 Package
- 6 Sample Tubes
- 4 AA Batteries
- Instruction manual
- Switch-adjustable for 110/220v 50/60Hz operation