



B-245/164



B-150/151/155/273

**제품설명**

- PH(수소이온농도지수) 및 ORP(mV) 측정
- 소형, 경량, 저가격 제품

**SPECIFICATIONS**

Model	No.Description
B-245	pH/mV Meter With Manual Temp. Compensation, covers 0-14.00 pH, 0-1,900 mV, -50 to 150 C Temp.
B-164	pH/mV Meter With Automatic Temp. Compensation, covers 0-14.00 pH, 0-1,900 mV, -50 to 150 C Temp., with temperature probe.

**제품설명**

- Conductivity(전도도) 및 TDS(총용존고형물) 측정
- 소형, 경량, 저가격 제품

**SPECIFICATIONS**

Model No.	Description
B-150	Multi-range Digital Conductivity/TDS Meter, Conductivity ranges 10, 100, 1,000, 10,000 micromhos/cm. TDS 7, 70, 700, 7,000 mg/L.
B-151	Multi-range Digital Conductivity/TDS Meter, Conductivity ranges 100, 1,000, 10,000, 100,000 micromhos/cm. TDS 70, 700, 7,000, 70,000 mg/L.
B-155	Single-range Digital Conductivity/TDS Meter, specify one range from 100, 1,000, 10,000 micromhos/cm. 100, 1,000, 10,000 ppm.
B-273	Single-range Digital Conductivity/TDS Meter, with Temperature Display and sensor. Specify one range from 100, 1,000, 10,000 micromhos/cm; 100, 1,000, 10,000 ppm.

**Digital Water Velocity Meter (유속계)****FP101 / 201****제품설명**

배수로, 용수로, 하천 등의 유속을 측정하는 장비로 저가격, 경량화 등이 장점이며 측정기 상단부의 LCD창 및 계기판은 초보자도 쉽게 측정이 가능하도록 제작되어 있습니다.

**SPECIFICATIONS**

Model.	FP101 / 201
Range	0.3 ~ 25 FPS (0.1-8 MPS)
Accuracy	0.1 FPS
Averaging	True digital running average Readings taken once per second.
Display	LCD
Sensor Type	Protected Turbo-Prop propeller with electro-magnetic pickup
Weight	2 pounds (10 lbs. U.S., 14 lbs. international shipping weight)
Length	FP101 : 3' to 6' FP201 : 5' to 15'
Materials	PVC, anodized aluminum, stainless steel bearing
Power	Internal watch type batteries/1 year life
Operating Temperature	0° to 120° F
Carrying Case	The Flow Probe is shipped in a padded carrying case.