

작업환경 소음측정기 (Dosimeter)

DC-11

Dosimeters 작업환경소음계

- DC-11 작업환경소음계는 휴대하기에 편리하며 각종 작업환경 소음으로부터의 근로자보호 및 작업환경개선 계획수립에 적합한 작업환경소음계입니다.
- DC-11 작업환경소음계는 함께 공급되는 소프트웨어와 함께 그래픽 및 수치 출력이 가능하며 저가격의 경제적인 작업환경 소음계입니다.



EMC-511

Set consisting of DC-11 sound exposure meter, CB-5 sound calibrator, TR-40 tripod and ML-50 transporting briefcase

SPECIFICATIONS

시양 / 제품번호	DC-11
Range	80 to 140 dBA (RMS) with A filter
Peak range	Up to 140 dB without weighting
Functions	Sound exposure (EAT), noise dose (%), daily equivalent continuous sound level (LAeq (daily)), peak (Lpk), equivalent continuous sound level (LAeq), statistical measurements, percentiles (L10, L50, L90), clock (indicates the duration of measurements).
Keyboard	Membrane keyboard with pass code to avoid accidental manipulation.
Standards	IEC 1252: 1993, IEC 60804: 1985 (A1: 1989, A2: 1993), UNE-EN 60804: 1994 (A2: 1994) class 2, EEC 86/188, Spanish royal decree law 1316: 1989.
Mark	CE
Battery	1 6LF22-type 9 V alkaline or lithium battery
Dimensions	140 × 82 × 23 mm
Weight	400 gr with battery
Accessories included	Case, 9 V battery, lapel microphone, connecting cable with PC, software for PC.



Main menu



Program's maker for the personal hearing protection



Data retrieval



Hearing protection database

software
PC
INCLUDED